



Deep Recessed Spot 7W, 15W & 24W



7-9W



Cut Out - Ø62mm

Technical Specifications

General

| | |
|-----------------------|------------------|
| System Wattage | 7W LED |
| Protection Class | IP20 |
| Driver Integrated | Constant Current |
| Input Voltage | 240Vac |
| Frequency | 50-60 Hz |
| Operating Voltage | 90-265Vac |
| Operating Temperature | 0-50°C |

Light Source

| | |
|---------------|---|
| Led Chip | Bridgelux, Citizen |
| CRI | Ra≥80 |
| LED CCT | 3000K/4000K/6500K Tuneable 3000K-6500K |
| Life Span | >50,000 Hours |
| System Lumens | 780 lm |
| Efficacy | 110 lm/W |

Physical



| | |
|----------|-------------------------|
| Body | Die Cast Aluminum |
| Optics | Polycarbonate Reflector |
| Mounting | Recess |

Driver

| | |
|------------------|----------------------------------|
| Power Factor | ≥0.95 |
| THD | <20% |
| Surge Protection | 2.5KV |
| Dimmable Options | Triac / 1-10V / Dali / RF remote |
| Efficiency | >75% |



12-15W



Cut Out - Ø77mm

Technical Specifications

General

| | |
|-----------------------|------------------|
| System Wattage | 15W LED |
| Protection Class | IP20 |
| Driver Integrated | Constant Current |
| Input Voltage | 240Vac |
| Frequency | 50-60 Hz |
| Operating Voltage | 90-265Vac |
| Operating Temperature | 0-50°C |

Light Source

| | |
|---------------|---|
| Led Chip | Bridgelux, Citizen |
| CRI | Ra≥80 |
| LED CCT | 3000K/4000K/6500K Tuneable 3000K-6500K |
| Life Span | >50,000 Hours |
| System Lumens | 1650 lm |
| Efficacy | 110 lm/W |

Physical



| | |
|----------|--------------------------------|
| Body | Die Cast Aluminum |
| Optics | Polycarbonate Reflector / Lens |
| Mounting | Recess |

Driver

| | |
|------------------|----------------------------------|
| Power Factor | ≥0.95 |
| THD | <20% |
| Surge Protection | 2.5KV |
| Dimmable Options | Triac / 1-10V / Dali / RF remote |
| Efficiency | >75% |



20-24W



Cut Out - Ø110mm

Technical Specifications

General

| | |
|-----------------------|------------------|
| System Wattage | 24W LED |
| Protection Class | IP20 |
| Driver Integrated | Constant Current |
| Input Voltage | 240Vac |
| Frequency | 50-60 Hz |
| Operating Voltage | 90-265Vac |
| Operating Temperature | 0-50°C |

Light Source

| | |
|---------------|---|
| Led Chip | Bridgelux, Citizen |
| CRI | Ra≥80 |
| LED CCT | 3000K/4000K/6500K Tuneable 3000K-6500K |
| Life Span | >50,000 Hours |
| System Lumens | 2650 lm |
| Efficacy | 110 lm/W |

Physical

| | |
|----------|--------------------------------|
| Body | Die Cast Aluminum |
| Optics | Polycarbonate Reflector / Lens |
| Mounting | Recess |

Driver

| | |
|------------------|----------------------------------|
| Power Factor | ≥0.95 |
| THD | <20% |
| Surge Protection | 2.5KV |
| Dimmable Options | Triac / 1-10V / Dali / RF remote |
| Efficiency | >75% |





